### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878. Issue date: 6/16/2022 Revision date: 12/23/2022 Supersedes version of: 6/16/2022 Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1. Product identifier**

Product form Product name

UFI

: Mixture
: LYRECO Correction fluid
: GV00-U05T-N00C-EME7

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

### Intended for general public

Main use category Use of the substance/mixture : Consumer use

: Correction fluid for paper or fax copies.

### 1.2.2. Uses advised against

No additional information available

### **1.3. Details of the supplier of the safety data sheet**

#### Distributor

Hainenko Limited Chase Road Southgate, 284 N14 6HF London United Kingdom T +44 20 8 882 8734 - F +44 20 8 882 7749 sales@hainenko.com

#### 1.4. Emergency telephone number

#### Emergency number

: +44 2088828734

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Edinburgh Centre) Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA	0344 892 0111	Only for healthcare professionals
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

SECTION 2: Hazards identification		
2.1. Classification of the substance or mixture		
Classification according to Regulation (EC) No. 1272/2008 [CLP]		
Flammable liquids, Category 3	H226	
Skin corrosion/irritation, Category 2	H315	
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411	
Full text of H- and EUH-statements: see section 16		

#### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements	
Labelling according to Regulation (EC) N	lo. 1272/2008 [CLP]
Hazard pictograms (CLP)	
Signal word (CLP)	GHS02 GHS07 GHS09 : Warning
Contains	<ul> <li>Warning</li> <li>Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).]</li> </ul>
Hazard statements (CLP)	: H226 - Flammable liquid and vapour.
	H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	<ul> <li>P102 - Keep out of reach of children.</li> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P261 - Avoid breathing vapours.</li> <li>P273 - Avoid release to the environment.</li> <li>P301+P330+P331+P310 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.</li> <li>Immediately call a POISON CENTER or doctor.</li> <li>P302+P352 - IF ON SKIN: Wash with plenty of soap and water.</li> <li>P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</li> </ul>
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Extra phrases	: For professional users only.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable
Labelling according to: exemption f	or packages of a capacity of 125ml or less
Hazard pictograms (CLP)	GHS02 GHS07 GHS09
Signal word (CLP)	: Warning
Hazardous ingredients	: Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F

to 374°F).]

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Hazard statements (CLP) Precautionary statements (CLP)	<ul> <li>H336 - May cause drowsiness or dizziness.</li> <li>P102 - Keep out of reach of children.</li> <li>P261 - Avoid breathing vapours.</li> <li>P501 - Dispose of contents and container to hazardous or special waste collection point, in</li> </ul>
	accordance with local, regional, national and/or international regulation. P301+P330+P331+P310 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor.
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Extra phrases	: For professional users only.
2.3. Other hazards	

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Calcium carbonate (471-34-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).] (64741-84-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

### 3.1. Substances

### Not applicable

#### 3.2. Mixtures

#### Comments

: Mixture. Solvent correction fluid, 20 ml, packed in plastic bottle with brush.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).] (Note P)	CAS-No.: 64741-84-0 EC-No.: 265-086-6 REACH-no: 01-2119485160- 44	35 – 45	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium carbonate	CAS-No.: 471-34-1 EC-No.: 207-439-9 REACH-no: 01-2119486795- 18	30 – 35	Not classified
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] substance with national workplace exposure limit(s) (AT, BE, BG, DK, EE, ES, FR, GB, GR, HR, IE, LT, LV, PL, PT, RO, SE, SK, IS, NO, CH) (Note V)(Note W)(Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-002 REACH-no: 01-2119489379- 17	10 – 15	Carc. 2, H351

Note P :	The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than
	0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be
	performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the
	precautionary statements (P102-)P260-P262-P301 + P310- P331 shall apply.
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium
	dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq$ 10 µm.
Note V:	If the substance is to be placed on the market as fibres (with diameter < 3 $\mu$ m, length > 5 $\mu$ m and aspect ratio ≥ 3:1) or particles
	of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must
	be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or
	additional routes of exposure (oral or dermal) should be applied.
Note W:	It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading
	to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the
	substance; it does not constitute a criterion for classification according to this Regulation.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water (for at least 15 minutes). If irritation persists, consult an eye specialist. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and e	ffects, both acute and delayed
Symptoms/effects Symptoms/effects after skin contact	<ul><li>May cause drowsiness or dizziness.</li><li>Irritation.</li></ul>

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	<ul><li>Water spray. Dry powder. Foam. Carbon dioxide.</li><li>Strong water jet.</li></ul>

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

5.2. Special hazards arising from the substance or mixture		
Fire hazard Hazardous decomposition products in case of fire	<ul><li>Flammable liquid and vapour.</li><li>Toxic fumes may be released. Carbon monoxide. Carbon dioxide.</li></ul>	
5.3. Advice for firefighters		
Firefighting instructions Protection during firefighting	<ul> <li>Cool down the containers exposed to heat with a water spray.</li> <li>Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.</li> </ul>	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for containment and cleaning up		
For containment	· Collect spillage	

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or
	public waters.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	<ul> <li>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Avoid breathing vapours. Avoid contact with skin and eyes.</li> <li>Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.</li> </ul>
7.2. Conditions for safe storage, including a	any incompatibilities
Storage conditions Packaging materials	<ul> <li>Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Avoid ignition sources.</li> <li>Original packaging.</li> </ul>
7.3. Specific end use(s)	
see section(s) : 1.2.	

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### 8.1.1 National occupational exposure and biological limit values

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Calcium carbonate (471-34-1)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> inhalable aerosol 4 mg/m <sup>3</sup> respirable aerosol
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m <sup>3</sup> respirable 10 mg/m <sup>3</sup> total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

Calcium carbonate (471-34-1)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	Hazard: not identified
Acute - systemic effects, inhalation	Hazard: not identified
Acute - local effects, dermal	Hazard: not identified
Acute - local effects, inhalation	Hazard: not identified
Long-term - systemic effects, dermal	Hazard: not identified
Long-term - local effects, dermal	Hazard: not identified
Long-term - systemic effects, inhalation	Hazard: not identified
Long-term - local effects, inhalation	6.36 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	Hazard: not identified
Acute - systemic effects, inhalation	Hazard: not identified
Acute - systemic effects, oral	6.1 mg/kg bodyweight
Acute - local effects, dermal	Hazard: not identified
Acute - local effects, inhalation	Hazard: not identified
Long-term - systemic effects,oral	6.1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	Hazard: not identified
Long-term - systemic effects, dermal	Hazard: not identified
Long-term - local effects, dermal	Hazard: not identified
Long-term - local effects, inhalation	1.06 mg/m <sup>3</sup>
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	Hazard: not identified
Acute - systemic effects, inhalation	Hazard: not identified

### Safety Data Sheet

titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
Acute - local effects, dermal	Hazard: not identified
Acute - local effects, inhalation	Hazard: not identified
Long-term - systemic effects, dermal	Hazard: not identified
Long-term - local effects, dermal	Hazard: not identified
Long-term - systemic effects, inhalation	Hazard: not identified
Long-term - local effects, inhalation	1.25 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	Hazard: not identified
Acute - systemic effects, inhalation	Hazard: not identified
Acute - systemic effects, oral	Hazard: not identified
Acute - local effects, dermal	Hazard: not identified
Acute - local effects, inhalation	Hazard: not identified
Long-term - systemic effects,oral	Hazard: not identified
Long-term - systemic effects, inhalation	Hazard: not identified
Long-term - systemic effects, dermal	Hazard: not identified
Long-term - local effects, dermal	Hazard: not identified
Long-term - local effects, inhalation	210 μg/m³
-	a solvent extraction process. It consists predominantly of aliphatic minantly in the range of C5 through C11 and boiling in the range of approxi
hydrocarbons having carbon numbers predom mately 35°C to 190°C (95°F to 374°F).] (64741-	minantly in the range of C5 through C11 and boiling in the range of approxi
hydrocarbons having carbon numbers predo mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers)	minantly in the range of C5 through C11 and boiling in the range of approxi 84-0)
hydrocarbons having carbon numbers predom mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal	minantly in the range of C5 through C11 and boiling in the range of approxi         84-0)         High hazard (no threshold derived)
hydrocarbons having carbon numbers predo mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers)	minantly in the range of C5 through C11 and boiling in the range of approxi         84-0)         High hazard (no threshold derived)         1286.4 mg/m³ Neurotoxicity Study
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal Acute - systemic effects, inhalation Acute - local effects, dermal	High hazard (no threshold derived) 1286.4 mg/m <sup>3</sup> Neurotoxicity Study Low hazard (no threshold derived)
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal Acute - systemic effects, inhalation Acute - local effects, dermal Acute - local effects, inhalation	minantly in the range of C5 through C11 and boiling in the range of approxi         84-0)         High hazard (no threshold derived)         1286.4 mg/m³ Neurotoxicity Study
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal Acute - systemic effects, inhalation Acute - local effects, dermal	High hazard (no threshold derived) 1286.4 mg/m <sup>3</sup> Neurotoxicity Study Low hazard (no threshold derived) 160.23 mg/m <sup>3</sup> Irritation (Respiratory tract)
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal Acute - systemic effects, inhalation Acute - local effects, inhalation Acute - local effects, inhalation Long-term - systemic effects, dermal	High hazard (no threshold derived) 1286.4 mg/m <sup>3</sup> Neurotoxicity Study Low hazard (no threshold derived) 160.23 mg/m <sup>3</sup> Irritation (Respiratory tract) 950 µg/kg bodyweight/day Repeated dose toxicity High hazard (no threshold derived)
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal Acute - systemic effects, inhalation Acute - local effects, dermal Acute - local effects, inhalation Long-term - systemic effects, dermal Long-term - local effects, dermal	<ul> <li>minantly in the range of C5 through C11 and boiling in the range of approxi 84-0)</li> <li>High hazard (no threshold derived)</li> <li>1286.4 mg/m<sup>3</sup> Neurotoxicity Study</li> <li>Low hazard (no threshold derived)</li> <li>160.23 mg/m<sup>3</sup> Irritation (Respiratory tract)</li> <li>950 µg/kg bodyweight/day Repeated dose toxicity</li> </ul>
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal Acute - systemic effects, inhalation Acute - local effects, dermal Acute - local effects, inhalation Long-term - systemic effects, dermal Long-term - local effects, dermal	<ul> <li>minantly in the range of C5 through C11 and boiling in the range of approxi 84-0)</li> <li>High hazard (no threshold derived)</li> <li>1286.4 mg/m<sup>3</sup> Neurotoxicity Study</li> <li>Low hazard (no threshold derived)</li> <li>160.23 mg/m<sup>3</sup> Irritation (Respiratory tract)</li> <li>950 µg/kg bodyweight/day Repeated dose toxicity</li> <li>High hazard (no threshold derived)</li> <li>1.9 mg/m<sup>3</sup> Repeated dose toxicity</li> </ul>
hydrocarbons having carbon numbers predor mately 35°C to 190°C (95°F to 374°F).] (64741-DNEL/DMEL (Workers)Acute - systemic effects, dermalAcute - systemic effects, inhalationAcute - local effects, dermalAcute - local effects, inhalationLong-term - systemic effects, dermalLong-term - local effects, dermalLong-term - systemic effects, inhalationLong-term - local effects, inhalationLong-term - local effects, inhalation	<ul> <li>minantly in the range of C5 through C11 and boiling in the range of approxi 84-0)</li> <li>High hazard (no threshold derived)</li> <li>1286.4 mg/m<sup>3</sup> Neurotoxicity Study</li> <li>Low hazard (no threshold derived)</li> <li>160.23 mg/m<sup>3</sup> Irritation (Respiratory tract)</li> <li>950 µg/kg bodyweight/day Repeated dose toxicity</li> <li>High hazard (no threshold derived)</li> <li>1.9 mg/m<sup>3</sup> Repeated dose toxicity</li> </ul>
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741- DNEL/DMEL (Workers) Acute - systemic effects, dermal Acute - systemic effects, inhalation Acute - local effects, dermal Acute - local effects, inhalation Long-term - systemic effects, dermal Long-term - local effects, dermal Long-term - systemic effects, inhalation Long-term - local effects, inhalation	High hazard (no threshold derived) 1286.4 mg/m <sup>3</sup> Neurotoxicity Study Low hazard (no threshold derived) 160.23 mg/m <sup>3</sup> Irritation (Respiratory tract) 950 µg/kg bodyweight/day Repeated dose toxicity High hazard (no threshold derived) 1.9 mg/m <sup>3</sup> Repeated dose toxicity 2.31 mg/m <sup>3</sup> Irritation (Respiratory tract)
hydrocarbons having carbon numbers predomately 35°C to 190°C (95°F to 374°F).] (64741-         DNEL/DMEL (Workers)         Acute - systemic effects, dermal         Acute - systemic effects, inhalation         Acute - local effects, dermal         Acute - local effects, inhalation         Long-term - systemic effects, dermal         Long-term - local effects, dermal         Long-term - local effects, inhalation         Dometerm - systemic effects, inhalation         Long-term - local effects, inhalation         Long-term - systemic effects, inhalation         Long-term - local effects, inhalation         Long-term - local effects, inhalation         Long-term - local effects, inhalation	High hazard (no threshold derived) 1286.4 mg/m <sup>3</sup> Neurotoxicity Study Low hazard (no threshold derived) 160.23 mg/m <sup>3</sup> Irritation (Respiratory tract) 950 µg/kg bodyweight/day Repeated dose toxicity High hazard (no threshold derived) 1.9 mg/m <sup>3</sup> Repeated dose toxicity 2.31 mg/m <sup>3</sup> Irritation (Respiratory tract) High hazard (no threshold derived)
hydrocarbons having carbon numbers predor mately 35°C to 190°C (95°F to 374°F).] (64741-DNEL/DMEL (Workers)Acute - systemic effects, dermalAcute - systemic effects, inhalationAcute - local effects, dermalAcute - local effects, dermalAcute - local effects, inhalationLong-term - systemic effects, dermalLong-term - local effects, dermalLong-term - local effects, inhalationDometerm - local effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, dermalAcute - systemic effects, dermalAcute - systemic effects, inhalationAcute - systemic effects, inhalation	High hazard (no threshold derived) 1286.4 mg/m <sup>3</sup> Neurotoxicity Study Low hazard (no threshold derived) 160.23 mg/m <sup>3</sup> Irritation (Respiratory tract) 950 µg/kg bodyweight/day Repeated dose toxicity High hazard (no threshold derived) 1.9 mg/m <sup>3</sup> Repeated dose toxicity 2.31 mg/m <sup>3</sup> Irritation (Respiratory tract) High hazard (no threshold derived)
hydrocarbons having carbon numbers predou mately 35°C to 190°C (95°F to 374°F).] (64741-DNEL/DMEL (Workers)Acute - systemic effects, dermalAcute - systemic effects, inhalationAcute - local effects, dermalAcute - local effects, dermalAcute - local effects, inhalationLong-term - systemic effects, dermalLong-term - local effects, dermalLong-term - local effects, inhalationLong-term - local effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, dermalAcute - systemic effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, oral	High hazard (no threshold derived)         1286.4 mg/m³ Neurotoxicity Study         Low hazard (no threshold derived)         160.23 mg/m³ Irritation (Respiratory tract)         950 µg/kg bodyweight/day Repeated dose toxicity         High hazard (no threshold derived)         1.9 mg/m³ Repeated dose toxicity         2.31 mg/m³ Irritation (Respiratory tract)         High hazard (no threshold derived)         1.9 mg/m³ Repeated dose toxicity         2.31 mg/m³ Irritation (Respiratory tract)         High hazard (no threshold derived)         1152 mg/m³ Neurotoxicity Study         25.6 mg/kg bodyweight/day Acute toxicity
hydrocarbons having carbon numbers predommately 35°C to 190°C (95°F to 374°F).] (64741-         DNEL/DMEL (Workers)         Acute - systemic effects, dermal         Acute - systemic effects, inhalation         Acute - local effects, dermal         Acute - local effects, inhalation         Long-term - systemic effects, dermal         Long-term - local effects, dermal         Long-term - local effects, inhalation         Long-term - local effects, inhalation         Acute - systemic effects, dermal         Acute - systemic effects, oral         Acute - local effects, dermal	High hazard (no threshold derived) 1286.4 mg/m <sup>3</sup> Neurotoxicity Study Low hazard (no threshold derived) 160.23 mg/m <sup>3</sup> Irritation (Respiratory tract) 950 µg/kg bodyweight/day Repeated dose toxicity High hazard (no threshold derived) 1.9 mg/m <sup>3</sup> Repeated dose toxicity 2.31 mg/m <sup>3</sup> Irritation (Respiratory tract) High hazard (no threshold derived) 1152 mg/m <sup>3</sup> Neurotoxicity Study 25.6 mg/kg bodyweight/day Acute toxicity Low hazard (no threshold derived)
hydrocarbons having carbon numbers predommately 35°C to 190°C (95°F to 374°F).] (64741-         DNEL/DMEL (Workers)         Acute - systemic effects, dermal         Acute - systemic effects, inhalation         Acute - local effects, dermal         Acute - local effects, inhalation         Long-term - systemic effects, dermal         Long-term - local effects, dermal         Long-term - systemic effects, inhalation         DNEL/DMEL (General population)         Acute - systemic effects, dermal         Acute - systemic effects, inhalation         DNet - systemic effects, inhalation         Acute - systemic effects, inhalation         Acute - systemic effects, inhalation         Acute - systemic effects, dermal         Acute - systemic effects, dermal         Acute - systemic effects, inhalation         Acute - local effects, dermal         Acute - local effects, dermal         Acute - local effects, dermal         Acute - local effects, inhalation	High hazard (no threshold derived)         1286.4 mg/m³ Neurotoxicity Study         Low hazard (no threshold derived)         160.23 mg/m³ Irritation (Respiratory tract)         950 µg/kg bodyweight/day Repeated dose toxicity         High hazard (no threshold derived)         1.9 mg/m³ Repeated dose toxicity         2.31 mg/m³ Irritation (Respiratory tract)         High hazard (no threshold derived)         1152 mg/m³ Neurotoxicity Study         25.6 mg/kg bodyweight/day Acute toxicity         Low hazard (no threshold derived)         1152 mg/m³ Neurotoxicity Study         25.6 mg/kg bodyweight/day Acute toxicity         Low hazard (no threshold derived)         143.5 mg/m³ Irritation (Respiratory tract)
hydrocarbons having carbon numbers predor mately 35°C to 190°C (95°F to 374°F).] (64741-DNEL/DMEL (Workers)Acute - systemic effects, dermalAcute - systemic effects, inhalationAcute - local effects, dermalAcute - local effects, inhalationLong-term - systemic effects, dermalLong-term - local effects, dermalLong-term - local effects, inhalationDNEL/DMEL (General population)Acute - systemic effects, inhalationLong-term - local effects, inhalationLong-term - local effects, inhalationAcute - systemic effects, inhalationAcute - systemic effects, oermalAcute - systemic effects, oralAcute - systemic effects, oralAcute - local effects, oralAcute - local effects, inhalationAcute - systemic effects, oralAcute - local effects, inhalationAcute - systemic effects, oralAcute - local effects, inhalationLong-term - systemic effects, oralAcute - local effects, inhalation	High hazard (no threshold derived)         1286.4 mg/m³ Neurotoxicity Study         Low hazard (no threshold derived)         160.23 mg/m³ Irritation (Respiratory tract)         950 µg/kg bodyweight/day Repeated dose toxicity         High hazard (no threshold derived)         1.9 mg/m³ Repeated dose toxicity         2.31 mg/m³ Irritation (Respiratory tract)         High hazard (no threshold derived)         1.9 mg/m³ Repeated dose toxicity         2.31 mg/m³ Irritation (Respiratory tract)         High hazard (no threshold derived)         1152 mg/m³ Neurotoxicity Study         25.6 mg/kg bodyweight/day Acute toxicity         Low hazard (no threshold derived)         1152 mg/m³ Neurotoxicity Study         25.6 mg/kg bodyweight/day Acute toxicity         Low hazard (no threshold derived)         143.5 mg/m³ Irritation (Respiratory tract)         30 µg/kg bodyweight/day Repeated dose toxicity

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).] (64741-84-0)

Long-term - local effects, dermal	High hazard (no threshold derived)
Long-term - local effects, inhalation	690 μg/m³ Irritation (Respiratory tract)

#### 8.1.5. Control banding

### No additional information available

8.2. Exposure controls
------------------------

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### 8.2.2.1. Eye and face protection

#### Eye protection: Not required for normal conditions of use

#### 8.2.2.2. Skin protection

**Skin and body protection:** Not required for normal conditions of use

#### 8.2.2.3. Respiratory protection

#### **Respiratory protection:**

Not required for normal conditions of use

#### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

Not required.

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

9.1. Information on basic physical and chemical properties		
Physical state Colour	: Liquid : white.	
Odour	: Mild odor.	
Odour threshold	: Not applicable	
Melting point	: Not applicable	
Freezing point	: Not applicable	
Boiling point	: 25 – 200 °C (Naphtha (petroleum), solvent-refined light: Source: ECHA)	
Flammability	: Not applicable	
Explosive limits	: 1.1 – 7.6 vol % (Naphtha (petroleum), solvent-refined light; SDS supplier)	
Lower explosion limit	: 1.1 vol % (Naphtha (petroleum), solvent-refined light, SDS supplier)	
Upper explosion limit	: 7.6 vol % (Naphtha (petroleum), solvent-refined light, SDS supplier)	
Flash point	: 55 – 65 °C (closed cup), Pensky - Martens, EN ISO 2719	
Auto-ignition temperature	: > 200 °C (Naphtha (petroleum), solvent-refined light; Source: ECHA)	
Decomposition temperature	: Not applicable	
рН	: Not applicable	
Viscosity, kinematic	: > 25 mm²/s (40 °C); calculated	
Solubility	: Water: Insoluble	
Partition coefficient n-octanol/water (Log Kow)	: Not applicable	

### SECTION 9: Physical and chemical properties

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Partition coefficient n-octanol/water (Log Pow) Vapour pressure Vapour pressure at 50°C Density Relative density Relative vapour density at 20°C Particle characteristics	<ul> <li>Not applicable</li> <li>4 – 240 kPa (Naphtha (petroleum), solvent-refined light: Source: ECHA)</li> <li>Not applicable</li> <li>1.1 – 1.2 g/cm<sup>3</sup> (pycnometer; (20+0.5)°C; EN ISO 2811)</li> <li>0.62 – 0.88 (Naphtha (petroleum), solvent-refined light; Source: ECHA)</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
9.2. Other information	

### 9.2.1. Information with regard to physical hazard classes

Explosion limits	: 1.1 – 7.6 vol % (Naphtha (petroleum), solvent-refined light; SDS supplier)
9.2.2. Other safety characteristics	
Other properties	: flow time : 30 - 35 s (cup 4 mm)
Solvent content	: 40 - 45 %

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

**10.3. Possibility of hazardous reactions** 

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

**10.5. Incompatible materials** 

No additional information available

**10.6. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (dermal) :	Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)
Calcium carbonate (471-34-1)	
LD50 oral rat > 2000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 3 mg/l 4 h
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat	> 6.82 mg/l

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

hydrocarbons obtained as the raffinate from a	ow boiling point modified naphtha; [A complex combination of a solvent extraction process. It consists predominantly of aliphatic minantly in the range of C5 through C11 and boiling in the range of approxi 84-0)	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401 method)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402 method)	
LC50 Inhalation - Rat > 5610 mg/l (OECD 403 method)		
Skin corrosion/irritation :	Causes skin irritation.	
Serious eye damage/irritation :	pH: Not applicable Not classified (Based on available data, the classification criteria are not met) pH: Not applicable	
Respiratory or skin sensitisation :	Not classified (Based on available data, the classification criteria are not met)	
Germ cell mutagenicity :	Not classified (Based on available data, the classification criteria are not met)	
Carcinogenicity :	Not classified. (Based on available data, the classification criteria are not met)	
Reproductive toxicity :	Not classified (Based on available data, the classification criteria are not met)	
STOT-single exposure :	May cause drowsiness or dizziness.	
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu m]$ (13463-67-7)	
NOAEL (oral, rat)	3500 mg/kg bodyweight 90 days	
NOAEC (inhalation, rat, dust/mist/fume)	10 mg/m³ 90 days	
hydrocarbons obtained as the raffinate from a	ow boiling point modified naphtha; [A complex combination of a solvent extraction process. It consists predominantly of aliphatic minantly in the range of C5 through C11 and boiling in the range of approxi 84-0)	
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure : Aspiration hazard :	Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)	
LYRECO Correction fluid		
Viscosity, kinematic	> 25 mm <sup>2</sup> /s (40 °C); calculated	
11.2. Information on other hazards		
11.2.1. Endocrine disrupting properties		
Adverse health effects caused by endocrine : disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %	

### 11.2.2. Other information

No additional information available

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general Hazardous to the aquatic environment, short–term (acute)	<ul> <li>Toxic to aquatic life with long lasting effects.</li> <li>Not classified (Based on available data, the classification criteria are not met)</li> </ul>
Hazardous to the aquatic environment, long-term (chronic) Not rapidly degradable	: Toxic to aquatic life with long lasting effects.

### Safety Data Sheet

Calcium carbonate (471-34-1)		
LC50 - Fish [1]	> 100 mg/l 96 h; (OECD 203 method)	
EC50 - Crustacea [1]	> 100 mg/l 48 h; Daphnia magna (Water flea); (OECD 202 method)	
EC50 72h - Algae [1]	> 14 mg/l 72 h; (OECD 201 method)	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7		
LC50 - Fish [1]	> 10000 mg/l Cyprinodon variegatus (sheepshead minnow); semi-static test; (OECD 203 method)	
LC50 - Fish [2]	> 1000 mg/l Pimephales promelas; static; EPA-540/9-85-006	
EC50 - Crustacea [1]	> 10000 mg/l copepod Acartia tonsa (ISO 14669 (1999); ISO 5667-16 (1998)	
EC50 - Crustacea [2]	> 1000 mg/l Daphnia magna (Water flea); static; (OECD 202 method)	
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata; Growth rate; static; (OECD 201 method)	
EC50 72h - Algae [2]	> 10000 mg/l Skeletonema costatum (marine diatom); ISO 10253	
NOEC	> 100000 mg/kg bw (Hyalella azteca; semi-static test; ASTM 1706)	
hydrocarbons obtained as the raffinate from a hydrocarbons having carbon numbers predor mately 35°C to 190°C (95°F to 374°F).] (64741-		
LL50, fish, Oncorhynchus mykiss (Rainbow trout)	10 mg/l (96 Hours)	
LL50, fish, Pimephales promelas	8.2 mg/l (96 Hours)	
EL50, Daphnia magna (Water flea)	4.5 mg/l (48 Hours)	
NOELR, Daphnia magna (Water flea)	2.6 mg/l (21 days)	
EL50, algae, Pseudokirchnerella subcapitata	3.1 mg/l (72 Hours)	
NOELR, algae, Pseudokirchnerella subcapitata	0.5 mg/l (72 Hours)	
EL50, microorganisms, Tetrahymena pyriformis	15.41 mg/l (40 Hours)	
12.2. Persistence and degradability		
Calcium carbonate (471-34-1)		
Persistence and degradability	The methods for determining biodegradability are not applicable to inorganic substances.	
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Persistence and degradability	Not relevant.	
Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).] (64741-84-0)		
Persistence and degradability	Study : Not readily biodegradable. simulation test : Biodegradable.	
12.3. Bioaccumulative potential		
LYRECO Correction fluid		
Partition coefficient n-octanol/water (Log Pow)	Not applicable	
Partition coefficient n-octanol/water (Log Kow)	Not applicable	
Calcium carbonate (471-34-1)		
Bioaccumulative potential	No information available.	

### Safety Data Sheet

titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Bioaccumulative potential	Does not accumulate in organisms.	
Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).] (64741-84-0)		
Partition coefficient n-octanol/water (Log Kow)	3 - 6	
Bioaccumulative potential	Forecast : bioaccumulative.	
12.4. Mobility in soil		
Calcium carbonate (471-34-1)		
Ecology - soil	No information available.	
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
Ecology - soil	immobile.	
hydrocarbons obtained as the raffinate from a	w boiling point modified naphtha; [A complex combination of a solvent extraction process. It consists predominantly of aliphatic minantly in the range of C5 through C11 and boiling in the range of approxi 84-0)	
Ecology - soil	No data available.	
12.5. Results of PBT and vPvB assessment		
Component		
Calcium carbonate (471-34-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).] (64741-84-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
12.6. Endocrine disrupting properties		
Adverse effects on the environment caused by endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.	
12.7. Other adverse effects		
Additional information :	Avoid release to the environment.	

### Safety Data Sheet

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods Additional information	<ul> <li>Dispose of contents/container in accordance with licensed collector's sorting instructions.</li> <li>Flammable vapours may accumulate in the container.</li> </ul>
SECTION 14: Transport information	
In accordance with ADR	
14.1. UN number or ID number	
UN-No. (ADR)	: UN 1263
14.2. UN proper shipping name	
Proper Shipping Name (ADR) Transport document description (ADR)	: PAINT RELATED MATERIAL : UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)	
ADR Transport hazard class(es) (ADR) Danger labels (ADR)	
14.4. Packing group	
Packing group (ADR)	: 111
14.5. Environmental hazards	
Dangerous for the environment Other information	: Yes : No supplementary information available
14.6. Special precautions for user	
Overland transport Classification code (ADR) Special provisions (ADR) Limited quantities (ADR) Excepted quantities (ADR) Packing instructions (ADR) Special packing provisions (ADR) Mixed packing provisions (ADR) Portable tank and bulk container instructions (ADR) Portable tank and bulk container special provisions (ADR) Tank code (ADR) Vehicle for tank carriage Transport category (ADR)	<ul> <li>F1</li> <li>163, 367, 650</li> <li>5l</li> <li>E1</li> <li>P001, IBC03, LP01, R001</li> <li>PP1</li> <li>MP19</li> <li>T2</li> <li>TP1, TP29</li> <li>LGBF</li> <li>FL</li> <li>3</li> <li>V12</li> </ul>
Special provisions for carriage - Packages (ADR) Special provisions for carriage - Operation (ADR) Hazard identification number (Kemler No.) Orange plates	<ul> <li>S2</li> <li>30</li> <li>30</li> <li>1263</li> <li>D/E</li> </ul>

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

### 14.7. Maritime transport in bulk according to IMO instruments

### Not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).]	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).]	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).]	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).]	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

#### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

### No chemical safety assessment has been carried out

#### For the following substances of this mixture a chemical safety assessment has been carried out:

Naphtha (petroleum), solvent-refined light; Low boiling point modified naphtha; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of aliphatic hydrocarbons having carbon numbers predominantly in the range of C5 through C11 and boiling in the range of approxi mately 35°C to 190°C (95°F to 374°F).]

### **SECTION 16: Other information**

#### Indication of changes:

Indication of cha	anges		
Section	Changed item	Change	Comments
	Revision date	Added	
	Supersedes	Added	
	Special provisions for carriage - Packages (ADR)	Added	
	Special provisions for carriage - Operation (ADR)	Modified	
	Tank code (ADR)	Modified	
	Portable tank and bulk container special provisions (ADR)	Modified	
	Portable tank and bulk container instructions (ADR)	Modified	
	Packing instructions (ADR)	Modified	
	Adverse health effects caused by endocrine disrupting properties	Added	
	CSR applicable	Added	
2.1	Adverse physicochemical, human health and environmental effects	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Extra phrases	Added	
2.2	Signal word (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after eye contact	Modified	
5.2	Fire hazard	Modified	

### Safety Data Sheet

Indication of changes			
Section	Changed item	Change	Comments
5.3	EAC code	Modified	
6.1	Emergency procedures	Modified	
7.1	Hygiene measures	Modified	
7.2	Packaging materials	Modified	
7.2	Storage conditions	Modified	
7.3	Specific end uses	Added	
9.1	Viscosity, kinematic	Added	
9.1	Relative vapour density at 20°C	Added	
9.1	Explosive limits (vol %)	Added	
9.1	Partition coefficient n-octanol/water (Log Kow)	Added	
9.1	Partition coefficient n-octanol/water (Log Pow)	Added	
9.1	Density	Modified	
9.1	Vapour pressure at 50°C	Added	
9.1	Relative density	Added	
9.1	Vapour pressure	Added	
9.1	Freezing point	Added	
9.1	рН	Added	
9.1	Decomposition temperature	Added	
9.1	Auto-ignition temperature	Added	
9.1	Lower explosion limit	Added	
9.1	Upper explosion limit	Modified	
9.1	Flash point	Modified	
9.1	Boiling point	Modified	
9.1	Odour threshold	Added	
9.2	Other properties	Added	
10.1	Reactivity	Modified	
10.4	Conditions to avoid	Modified	
12.3	Partition coefficient n-octanol/water (Log Kow)	Added	
12.3	Partition coefficient n-octanol/water (Log Pow)	Added	
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added	
14.6	Hazard identification number (Kemler No.)	Modified	
14.6	Transport category (ADR)	Modified	
14.6	Special provisions (ADR)	Modified	
14.6	Excepted quantities (ADR)	Modified	

Abbreviations and acronyms:	
ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	

### Safety Data Sheet

Abbreviations and a	cronyms:
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Carc. 2	Carcinogenicity, Category 2	

### Safety Data Sheet

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Full text of H- and EUH-statements:		
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.	
Flam. Liq. 2	Flammable liquids, Category 2	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H351	Suspected of causing cancer.	
H411	Toxic to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

### The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

### Safety Data Sheet

Annex to the safety data sheet			
Identified Uses	Es N°	Short title	Page
Formulation & (re)packing of substances and mixtures	1		21

Annex to the safety data sheet: Exposure scenario

Product form: Mixture Physical state: Liquid

### 1. 9.4.1a. - Formulation; Formulation & (re)packing of substances and mixtures

### 1.1. Title section

Formulation & (re)packing of substances and mixtures		
ES Ref.: 9.4.1a. ES Type: Worker		

Environment		Use descriptors
	Contributing scenario controlling environmental exposure	ERC2, ESVOC SPERC 2.2.v1

Worker		Use descriptors
	Contributing scenario controlling worker exposure	PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

	Formulation of the substance and its mixtures in batch or continuous operations within closed or contained systems, including incidental exposures during storage, materials transfers, mixing, maintenance, sampling and associated laboratory activities
Assessment method	See Section 3

### **1.2. Conditions of use affecting exposure**

# 1.2.1. Control of environmental exposure: Contributing scenario controlling environmental exposure (ERC2, ESVOC SPERC 2.2.v1)

ERC2	Formulation into mixture
ESVOC SPERC 2.2.v1	Formulation & packing of preparations and mixtures: Industrial (SU10)

Product (article) characteristics	
Physical form of product	Substance is complex UVCB, Predominantly hydrophobic

Amount used, frequency and duration of use (or from service life)		
Fraction of EU tonnage used in region:	0.1	
Regional use tonnage:	16500000 t/yr	
Fraction of Regional tonnage used locally:	0.0018	
Annual site tonnage:	30000 t/yr	
Maximum daily site tonnage	100000 kg/day	
Continuous release		
Emission Days (days/year)	300	

Technical and organisational conditions and measures	
Common practices vary across sites thus conservative process release estimates used	
Prevent discharge of undissolved substance to or recover from onsite wastewater. Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation). If discharging to municipal sewage treatment plant, no onsite wastewater treatment required.	

## Annex to the safety data sheet: Exposure scenario Product form: Mixture Physical state: Liquid

Technical and organisational conditions and measures		
Treat air emission to provide a typical removal efficiency of	56.5 %	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of	≥ 94.7 %	
If discharging to municipal sewage treatment plant, provide the required onsite wastewater removal efficiency of	≥ 0 %	
Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.		

Conditions and measures related to sewage treatment plant	
Estimated substance removal from wastewater via municipal sewage treatment	95.5 %
Total efficiency of removal from wastewater after onsite and offsite municipal treatment plant) RMMs	95.5 %
Maximum allowable site tonnage (MSafe)	100000 kg/d
Assumed domestic sewage treatment plant flow	2000 m³/d

Conditions and measures related to treatment of waste (including article waste)	
External treatment and disposal of waste should comply with applicable local and/or national regulations	
External recovery and recycling of waste should comply with applicable local and/or national regulations	

Other conditions affecting environmental exposure		
Local freshwater dilution factor:	10	
Local marine water dilution factor:	100	
Release fraction to soil from process (initial release prior to RMM):	0.025	
Release fraction to wastewater from process (initial release prior to RMM):	0.002	
Release fraction to soil from process (initial release prior to RMM):	0.0001	

### 1.2.2. Control of worker exposure: Contributing scenario controlling worker exposure (PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15)

PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises
PROC5	Mixing or blending in batch processes
PROC8a	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities

## Annex to the safety data sheet: Exposure scenario Product form: Mixture Physical state: Liquid

PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC14	Tabletting, compression, extrusion, pelettisation, granulation
PROC15	Use as laboratory reagent

Product (article) characteristics	
Physical form of product	Liquid
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently)
Vapour pressure	Liquid, vapour pressure > 10 kPa at Standard Temperature and Pressure

Amount used (or contained in articles), freque	ency and duration of use/exposure
Covers daily exposures up to 8 hours	

Technical and organisational conditions and measures		
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop	
General exposures (closed systems)	No other specific measures identified	
General exposures (closed systems),with sample collection	No other specific measures identified	
General exposures (open systems)	Provide extract ventilation to points where emissions occur	
Process sampling	No other specific measures identified	
Mixing operations, Closed systems	Provide extract ventilation to points where emissions occur	
Laboratory activities	Handle in a fume cupboard or under extract ventilation	
Bulk transfers	Ensure material transfers are under containment or extract ventilation	
Manual, Transfer from/pouring from containers	Ensure material transfers are under containment or extract ventilation	
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation	
Drum and small package filling	Fill containers/cans at dedicated fill points supplied with local extract ventilation	
Equipment cleaning and maintenance	No other specific measures identified	
Storage	No other specific measures identified	

Other conditions affecting workers exposure	
Assumes use at not more than 20°C above ambient temperature, Assumes a good basic standard of occupational hygiene is implemented	

Annex to the safety data sheet: Exposure scenario

Product form: Mixture Physical state: Liquid

### **1.3. Exposure estimation and reference to its source**

## 1.3.1. Environmental release and exposure Contributing scenario controlling environmental exposure (ERC2, ESVOC SPERC 2.2.v1)

#### Information for contributing exposure scenario

Hydrocarbon Block Method (Petrorisk)

## 1.3.2. Worker exposure Contributing scenario controlling worker exposure (PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15)

Information for contributing exposure scenario

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated

#### 1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 1.4.1. Environment

details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html)
---

Guidance - Health	Predicted exposures are not expected to exceed the DN(M)EL when the Risk
	Management Measures/Operational Conditions outlined in Section 2 are implemented.
	Where other Risk Management Measures/Operational Conditions are adopted, then users
	should ensure that risks are managed to at least equivalent levels. Available hazard data
	do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do
	not support the need for a DNEL to be established for other health effects. Risk
	Management Measures are based on qualitative risk characterisation